

Valentino MM, Kyser TK, Leybourne MI, Kotzer TG, Quirr DH, Lypaczewski P, Ansdell K, Wasyliuk K, 2017, Mineral chemistry of fracture coatings in Athabasca Group sandstone as records of element dispersion, Abstract, PDAC-SMC, Toronto, ON

The McArthur River deposit is a well-documented unconformity-related uranium deposit that is located in the southeastern portion of the Athabasca Basin in Saskatchewan, Canada. Samples of Athabasca Group sandstone containing fractures were selected from drill core of the Manitou Falls Formation. The core samples were collected to reflect a spectrum of fracture coating types within a vertical depth range from ~11 m to 593 m, over a horizontal extent of ~3150 m, and from near-ore to unmineralized areas, to compare McArthur River area fracture coating mineral chemistry to the Athabasca Group background signature. Because the fracture coatings record precipitation from various fluids associated with both syn-mineralization and post-mineralization dispersion, as well as from diagenetic background fluids of the Athabasca Group, the main objective of the study is to determine whether the fracture coatings and their immediate wall rocks provide evidence for migration to the surface of components from the U mineralization at depth. Seven types of fracture fillings were identified, representing various colors, mineralogies, and chemical features, as revealed by optical petrography, scanning electron microscopy, X-ray diffraction, shortwave infrared reflectance spectroscopy, and geochemical analysis. Weak acid leach (2% HNO₃) and aqua regia were used to leach mobile elements, followed by high-resolution inductively-coupled plasma mass spectrometry to obtain the bulk fracture coating geochemistry. Continuous leach inductively-coupled plasma mass spectrometry (CL-ICP-MS) was used to determine the relationship between trace elements, including Pb isotopes, and their release from specific mineral phases in real-time through leaching by progressively reactive solutions from water to 30% nitric. The ²⁰⁷Pb/²⁰⁶Pb ratios of fracture coatings and of wall rock reflect the effect post-mineralization dispersion of components from the deposit into the near-fracture sandstone (low ²⁰⁷Pb/²⁰⁶Pb values), as shown by gradational changes in Pb isotopic ratio values from anomalous adjacent to the fracture surface to background values away from the fracture surface. This dispersion was followed by a less radiogenic fluid from which the fracture coatings, containing higher ²⁰⁷Pb/²⁰⁶Pb values, were deposited. Hyperspectral imaging of fracture coatings shows the presence of various layers of alteration minerals that reflect precipitation from multiple fluid events on many fractures. Fracture coatings can be used to detect dispersion from U mineralization at depth through geochemical and mineralogical analyses. This research indicates that the footprint of the deposit extends upwards through some fracture networks and may be detectable in analyses of overlying surficial media.

NSERC-CMIC Mineral Exploration Footprints Project Contribution 122.